



ESAL d.o.o., Anhovo 9, SI-5210 Deskle, www.esal.si
06

Standard <i>Norm</i> <i>Norme</i>	EN 494
Product	Fibre-cement corrugated sheets EFASAL Profile 8
<i>Produkt</i> <i>Produit</i>	<i>Faserzement Wellplatten EFASAL Profil 8</i> <i>Plaques ondulée en fibres-ciment EFASAL profil 8</i>
Intended use <i>Anwendung</i> <i>Usage</i>	Corrugated sheets for façade clading <i>Wellplatten zur Bekleidung von Fassaden</i> <i>Plaques ondulée pour revêtement de façade</i>
Type <i>Typ</i> <i>Type</i>	NT
Pitch / height of corrugation <i>Wellenbreite / Wellenhöhe</i> <i>Largeur / hauteur de l' onde</i>	130 mm / 30 mm
Category and class <i>Kategorie und Klasse</i> <i>Catégorie et classe</i>	B1X
Fire classification <i>Brandverhalten</i> <i>Classement feu</i>	A2-s1, d0



**ESAL d.o.o., Anhovo 9, SI-5210 Deskle, www.esal.si
06**

Norma	EN 494
Produkt	Płyty faliste z cementu włóknistego EFASAL profil 8 [Profile 8]
Przeznaczenie	Płyty faliste na okładziny fasad
Typ	NT
Szerokość/wysokość karbowania	130 mm / 30 mm
Kategoria i klasa	B1X
Klasyfikacja ogniowa	A2-s1, d0